



TOLERANCES UNLESS OTHERWISE SPECIFIED		ROUGHNESS		EXTERNAL FORM		SIZE		MATERIAL		QTY		REMARKS	
Ø38h6 +0.016 -0.011		Ø60m6 +0.030 -0.011		NO.		DESCRIPTIONS		DRAWN		DESIGNED		CHECKED	
DIMENSION		TOL.		SYMBOLS		PART NAME		DATE		DWG. NO.		REL. NO.	
TOLERANCE		TOL.		SYMBOLS		PART NAME		DATE		DWG. NO.		REL. NO.	
4°	16°	±0.2	0.08	▽▽▽	0.08	5.5KW 6P 1/21~1/30	K.E.J	2007.10.11		7H6P30-L2125			
16°	68°	±0.3	0.08	▽▽▽	0.08	JK-LT 2125 REDUCER	K.W.S						
68°	125°	±0.4	0.08	▽▽▽	0.08								
125°	250°	±0.5	0.08	▽▽▽	0.08								
250°	500°	±0.6	0.08	▽▽▽	0.08								
500°	1000°	±0.8	0.08	▽▽▽	0.08								
1000°	2000°	±1.0	0.08	▽▽▽	0.08								
2000°	4000°	±1.5	0.08	▽▽▽	0.08								
ANGLE		±0.5	0.08	▽	0.08								